

PRODUCT DATA SHEET

SURFACE SPECIALITY CHEMIE

K-GLOSS 98B

It is a multifunctional filler additive works in pigment space theory in major solvent based and water based coatings.

Physical & chemical Data

Appearance: White free flow powder

Brightness : more than 90 %

PH of solution: 7

Chemical Nature: super ultra fine modified layered silicate of aluminum

Refractive Index: 1.56

Specific Gravity: 2.63


Oil Absorption: 42

Average Particle Size: 0.2 micron in serigraph

APPLICATION:

Used as pigment extension agent in solvent and water based system, replace TiO₂ and others pigment as well.

- ✓ All type paints & primers, and Liquid Ink.
- ✓ All type paste Ink, Plastisol, silkscreen Ink
- ✓ Satin finish Coatings In both Water and solvent also in Oil based system.
- ✓ Wood, metal, glass putty and fillers or sealer
- ✓ White correction fluid or others color
- ✓ Polishes
- ✓ Wood coating
- ✓ Epoxy ceramic coatings
- ✓ Epoxy putty



DOSAGES:

FUNCTION	PAINTS	LQ INK	PASTE INK	FILLER	PAPER COATING	CORRECTION FLUID
TiO2 extent	10-35	20-35	10-25	30-45%	35-45	35-40
Anti settling	2-5	2-6	25-30	-	same	42-45
Dispersion	1-5	2-5	3-6	8-10	10-15	10-15
Water Resistance	1-5	1-6	2-6	3-8	3-8	3-8
Sandibility	2-3	2-5	2-5	7-9	5-6	7-8
Reinforce	4-5	3-7	3-8	8-15		

STORAGE & SELF LIFE:

Keep the material tightly closed condition in dark cool places.
Self life is two years from manufacturing date.

Products Origin: It is formulated and distributed by surface speciality Chemie

PACKING:

22.68 KGS PACK,



CUSTOMER CARE OR SERVICE CALL: 00-91-9830665596

13 Nager bazaar Road, Gr.Floor Kolkata.700074, West Bengal, India
Email: sschemie.ar@gmail.com, info@sschemie.co.in
URL: www.sschemie.co.in
PHONE: 9830665596
TELE-00-91-25605161
Unit: Vill-Bodai, PO-Jugberia, Dist-24 PGS, Kolkata-700110, West Bengal India
Issue of Data sheet 2017 Nov